

AT-PP □□□ □□□

KT □□□ □□□□ □ PushPull □□□□ / IP65



IP54

HL3
EN 45549-2

IP55

ECOLAB
certified

IP64

UV
ISO 4892-2A

IP65

RoHS
compliant

UL US

REACH
COMPLIANCE

RIFA

Made in
Germany


IP □□□□ (EN 60529)	IP54, IP55, IP64, IP65
	□□□□□ □□□ □□□□□
	UL94-V0, □□□□□
	-40 C° to 90 C°
	□□□ □□, □□□□□

□□ □□ □ □□

AT-PP □□□□ KT □□□ □□□ □□□□□ □□□□□ □□□□ □□□□ □□□ □□□□. Pushpu
AT-PP□□□□ □□□□ □□□ □□□ □□□ □□□□□ □□□□ □□□ □ □□ □□□□□ □□□ □□□□□ □□□ □ □□
PushPull □□ □ add-on housing□ □□ □□ □□ □□□.

□□ □ □□

- By utilising the AT-PP grommet, connectors can be integrated directly into the cable entry frame
- □□□ □□□ □□ □□
- □□□□□ □□□
- Grommet is suitable for PushPull housings
- Cost-saving assembly



EAN

□□ □□

39961
4251269322570
5
42 mm
41,5 mm
19 mm
2 mm